

HOT SPOT[®] COLLECTION

TX



2

People

11

Jets

Open

Seating

115 or 230

Voltage

6' x 6' x 29"

Dimensions

FROG[®] In-Line Cartridge Ready

Water Care

HOT SPOT® COLLECTION

TX




TX spa shown with Alpine White shell, and Storm cabinet.

Shell Colors



Cabinet Colors



Cover Colors



Seating Capacity	2 people	Control System	IQ 2020® 115 V / 15 amp,** 60 Hz (Includes G.F.C.I. protected power cord) or 115 V / 30 amp*** or 230 V / 50 amp*** 60 Hz
Dimensions	6' x 6' x 29" / 1.83 m x 1.83 m x 0.74 m	Lighting – Interior	4 multi-color LED points of light, dimmable
Water Capacity	190 gallons / 720 liters	Heater	No-Fault® 1,000 W / 115 V or 4,000 W / 230 V
Weight	635 lbs. / 290 kg dry; 2,570 lbs. / 1,165 kg filled*	Energy Efficiency	FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas
Jets (All with stainless steel trim)	11 total <ul style="list-style-type: none"> • 1 Moto-Massage® jet • 1 Directional Hydromassage jet • 1 Rotary Hydromassage jet • 8 Directional Precision® jets 	Effective Filtration Area	30 sq. ft., top loading
Jet Pump	Wavemaster® 4200; Two-speed, 1.0 HP Continuous Duty, 1.7 HP Breakdown Torque	Vinyl Cover	3.5" to 2.5" tapered, 1.5 lb. density foam core
Circulation Pump (Optional)	SilentFlo® 5000	Cover Lifter (Optional)	CoverCradle®, CoverCradle II, or UpRite®
Floor Drain	Included	Steps (Optional)	Everwood® - Almond, Havana, and Storm Polymer - Ash
Water Care System	FROG® In-Line Cartridge Ready		

Actual colors and products may vary from print representation. See dealer to verify. *Includes water and 2 adults weighing 175 lbs. each. **Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S. *** G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater. © 2020 Watkins Wellness • Rev. C